




# REVERSED EYE WEB SLINGS




TYPE 6 - REVERSED EYE



## MEDIUM DUTY (600 WEBBING)

| WIDTH  | ID CODE | PLY | RATED CAPACITY IN POUNDS  |   |   | EYE SIZE | WEIGHT IN LBS. |        |
|--------|---------|-----|---|---|---|----------|----------------|--------|
|        |         |     | VERTICAL<br> | CHOKER<br> | BASKET<br> |          | 5' base        | add/ft |
| 2"     | 62RE1   | 1   | 3600  | 2900  | 7200  | 9"       | .875           | .16    |
| 3 1/2" | 635RE1  | 1   | 5000  | 4000  | 10000   | 12"      | 1.840          | .32    |
| 4"     | 64RE1   | 1   | 6800  | 5400  | 13600   | 12"      | 2.200          | .34    |
| 6"     | 66RE1   | 1   | 8000  | 6400  | 16000   | 15"      | 2.860          | .55    |
| 2"     | 62RE2   | 2   | 5200  | 4200  | 10400   | 12"      | 1.300          | .24    |
| 3 1/2" | 635RE2  | 2   | 7800  | 6200  | 15600   | 12"      | 2.800          | .46    |
| 4"     | 64RE2   | 2   | 10500   | 8400  | 21000   | 12"      | 2.980          | .50    |
| 6"     | 66RE2   | 2   | 14400   | 11500   | 28800   | 15"      | 4.540          | .81    |

## HEAVY DUTY (900 WEBBING)

| WIDTH  | ID CODE | PLY | RATED CAPACITY IN POUNDS  |   |   | EYE SIZE | WEIGHT IN LBS. |        |
|--------|---------|-----|---|---|---|----------|----------------|--------|
|        |         |     | VERTICAL<br> | CHOKER<br> | BASKET<br> |          | 5' base        | add/ft |
| 2"     | 92RE1   | 1   | 4500  | 3600  | 9000  | 9"       | 1.160          | .21    |
| 3 1/2" | 935RE1  | 1   | 6000  | 4800  | 12000   | 12"      | 2.310          | .37    |
| 4"     | 94RE1   | 1   | 7700  | 6200  | 15400   | 12"      | 2.560          | .40    |
| 6"     | 96RE1   | 1   | 11000   | 8800  | 22000   | 15"      | 3.260          | .64    |
| 2"     | 92RE2   | 2   | 6500  | 5200  | 13000   | 12"      | 1.840          | .32    |
| 3 1/2" | 935RE2  | 2   | 9400  | 7300  | 18800   | 12"      | 3.200          | .49    |
| 4"     | 94RE2   | 2   | 13000   | 10400   | 26000   | 12"      | 3.740          | .62    |
| 6"     | 96RE2   | 2   | 20000   | 16000   | 40000   | 15"      | 5.380          | .89    |

NOTE: Angles of less than 30° will not be used  
REFER TO ANGLE EFFICIENCY CHART

NOTE: RE = Twisted eye is standard (Type 6)  
FE = Flat eye special (specify Type 7)

## SLING PROTECTION

Wear pads and sleeves give a sling extra protection at expected wear points. Available in light polyester and nylon (Cordura), heavy nylon, heavy polyester, and leather.

### TYPE A:

This wear pad is sewn directly in place to give fixed protection where it wears the most.



### TYPE B:

Sliding sleeve wear pad can be positioned anywhere on the sling. Ideal for handling sharp loads.



ALSO AVAILABLE  
is open face & velcro  
adjustable sleeve  
type d - not shown.

### TYPE C:

Edge wrap wear pad is sewn along both edges of the sling to protect from edge wear and cutting.



Observe rated capacity.

**! WARNING!**

Work load limits will be reduced when less than 90° from horizontal (See Efficiency Chart). Angles of less than 30° are not to be used. Inspect before use. Additional requirements and safe operating practices are outlined in current OSHA, Federal Register Part 29, 1910.184 and ASME B30.9 c-2000. Death or injury can occur from improper use or maintenance!